







Fiber Optic Splice Closure

Vertical System

Image	P/No	Type	Description
	TCFOSDA	Vertical Fiber Optic Splice Closure	Outside Dimension: 480*455*130 (mm) Weight: 2600g-2800g Entry / Exit: 5 (pieces) Cable Diameter: Φ10—Φ22 (mm) Max Capacity: Bunchy: 96 (cores)
	TCFOSDB	Vertical Fiber Optic Splice Closure	Outside Dimension: 475x455x135 (mm) Weight: 2450g-2550g Entry / Exit: 2 (pieces) on each side (total 2 pieces) Cable Diameter: Φ10—Φ20 (mm) Max Capacity: Bunchy: 96 (cores)
	TCFOSDC	Vertical Fiber Optic Splice Closure	Outside Dimension: 475x450x140 (mm) Weight: 1800g-2000g Entry / Exit: 8 (pieces) Cable Diameter: Φ10—Φ22 (mm) Max Capacity: Bunchy: 96 (cores)
	TCFOSDD	Vertical Fiber Optic Splice Closure	Outside Dimension: 720x510x210 (mm) Weight: 4000g-4500g Entry / Exit: 6 (pieces) Cable Diameter: Φ10—Φ22 (mm) Max Capacity: Bunchy: 144 (cores)
	TCFOSDCE	Vertical Fiber Optic Splice Closure	Outside Dimension: 475x460x140 (mm) Weight: 1900g-2100g Entry / Exit: 5 (pieces) Cable Diameter: Φ10—Φ22 (mm) Max Capacity: Bunchy: 96 (cores)
	TCFOSCDF	Vertical Fiber Optic Splice Closure	Outside Dimension: 475x440x130 (mm) Weight: 2100g-2350g Entry / Exit: 5 (pieces) Cable Diameter: Φ10—Φ22 (mm) Max Capacity: Bunchy: 96 (cores)